

# NORTH KITSAP SCHOOL DISTRICT

# NEW PORTABLE INSTALLATION

HILDER PEARSON ELEMENTARY SCHOOL 15650 CENTRAL VALLEY RD NW, POULSBO, WA 98370 PROJECT NO. FANKS004





## DRAWING INDEX

### PROJECT TEAM

NORTH KITSAP SCHOOL DISTRICT 1365 FINN HILL ROAD POULSBO, WA 98370

OWNER'S PROJECT MANAGER: RICK GEHRKE 1365 FINN HILL ROAD POULSBO, WA 98370 OFC:(360) 396-3063 CELL: (360) 900-9839 FAX: (360) 396-3990

CIVIL AND ELECTRICAL ENGINEERS: ART ANDERSON ASSOCIATES, INC. 830 PACIFIC AVE. BREMERTON, WA 98337 OFC: (360) 479-5600 hgabales@artanderson.com


LAND SURVEYOR: PARAMETRIX, INC. 60 WASHINGTON AVE., STE 390 BREMERTON, WA 98337

OFC: (360) 377-0014

FINAL RE-SUBMITTAL 2020-JUL-29

SHEET IS 22x34 ANSI D IF PRINTING 11x17 USE 50% SCALE FACTOR

Permit Number: 20-02306



EW POR CENTRAL HILDER

MWM DRAWN: DESIGNED: CHECKED:

ISSUE DATE

29 JUL 2020

REVISIONS

JOB NO FANKS004

SHT TITLE TITLE SHEET, LOCATION MAPS, DRAWING INDEX &

PROJECT TEAM

SHT NO 1 OF 7

#### **TESC NOTES**

#### GENERAL EROSION AND SEDIMENTATION CONTROL NOTES

- 1. THE FOLLOWING EROSION AND SEDIMENTATION CONTROL NOTES APPLY TO ALL CONSTRUCTION SITE ACTIVITIES AT ALL TIMES, UNLESS OTHERWISE SPECIFIED ON THESE PLANS.
- 2. THE OWNER AND HIS/HER CONTRACTOR SHALL BE RESPONSIBLE AT ALL TIMES FOR PREVENTING SILT-LADEN RUNOFF FROM DISCHARGING FROM THE PROJECT SITE. FAILURE BY THE OWNER AND/OR CONTRACTOR CAN RESULT IN A FINE. THE DESIGNATED TEMPORARY CONTACT PERSON NOTED ON THIS PLAN SHALL BE AVAILABLE FOR CONTACT BY TELEPHONE ON A 24-HOUR BASIS THROUGHOUT CONSTRUCTION AND UNTIL THE PROJECT HAS BEEN COMPLETED AND ACCEPTED BY THE COUNTY.
- 3. STABILIZE EXPOSED AND UNWORKED SOILS BY APPLICATION OF EFFECTIVE BMPS THAT PREVENT EROSION APPLICABLE BMPS INCLUDE. BUT ARE NOT LIMITED TO: TEMPORARY AND PERMANENT SEEDING, SODDING, MULCHING, PLASTIC COVERING, EROSION CONTROL FABRICS AND MATTING, SOIL APPLICATION OF POLYACRYLAMIDE (PAM), THE EARLY APPLICATION OF GRAVEL BASE ON AREAS TO BE PAVED, AND DUST CONTROL.
- 4. CONTROL STORMWATER VOLUME AND VELOCITY WITHIN THE SITE TO MINIMIZE SOIL EROSION.
- 5. CONTROL STORMWATER DISCHARGES, INCLUDING BOTH PEAK FLOW RATES AND TOTAL STORMWATER VOLUME TO MINIMIZE EROSION AT OUTLETS AND TO MINIMIZE DOWNSTREAM CHANNEL AND STREAM BANK EROSION.
- 6. SOILS MUST NOT REMAIN EXPOSED AND UNWORKED FOR MORE THAN THE TIME PERIODS SET FORTH BELOW TO PREVENT EROSION:
  - 6.A. DURING THE DRY SEASON (MAY 1 SEPTEMBER 30): 7 DAYS
  - 6.B. DURING THE WET SEASON (OCTOBER 1 APRIL 30): 2 DAYS
- 7. STABILIZE SOILS AT THE END OF THE SHIFT BEFORE A HOLIDAY OR WEEKEND IF NEEDED BASED ON THE WEATHER FORECAST.
- 8. STABILIZE SOIL STOCKPILES FROM EROSION, PROTECT WITH SEDIMENT TRAPPING MEASURES, AND WHERE POSSIBLE, LOCATE AWAY FROM STORM DRAIN INLETS, WATERWAYS AND DRAINAGE CHANNELS.
- MINIMIZE THE AMOUNT OF SOIL EXPOSED DURING CONSTRUCTION ACTIVITY.
- 10. MINIMIZE THE DISTURBANCE OF STEEP SLOPES.
- 11. MINIMIZE SOIL COMPACTION AND, UNLESS INFEASIBLE, PRESERVE TOPSOIL
- 12. ALL EROSION AND SEDIMENTATION CONTROL MEASURES SHALL BE INSPECTED BY THE OWNER AND/OR CONTRACTOR ON A FREQUENT BASIS AND IMMEDIATELY AFTER EACH RAINFALL, AND MAINTAINED AS NECESSARY TO INSURE THEIR CONTINUED FUNCTIONING. ALL SEDIMENT SHALL BE REMOVED FROM SILT FENCES, STRAW BALES, SEDIMENT PONDS, ETC. PRIOR TO THE SEDIMENT REACHING  $\frac{1}{3}$  OF ITS MAXIMUM POTENTIAL DEPTH.
- 13. AT NO TIME SHALL CONCRETE, CONCRETE BY-PRODUCTS, VEHICLE FLUIDS, PAINT, CHEMICALS, OR OTHER POLLUTING MATTER BE PERMITTED TO DISCHARGE TO THE TEMPORARY OR PERMANENT DRAINAGE SYSTEM, OR TO DISCHARGE FROM THE PROJECT SITE.
- 14. REDIRECT SHEET FLOW, BLOCK DRAIN INLETS AND/OR CURB OPENINGS IN PAVEMENT AND INSTALL FLOW DIVERSION MEASURES TO PREVENT CONSTRUCTION SILT LADEN RUNOFF AND DEBRIS FROM ENTERING EXCAVATIONS AND FINISH SURFACES FOR BIORETENTION FACILITIES AND PERMEABLE PAVEMENTS.
- 15. INSTALL FLOW DIVERSION MEASURES OUTSIDE OF THE CRITICAL ROOT ZONE OF TREES TO BE PROTECTED. AT NO TIME SHALL CONSTRUCTION STORMWATER BE DIRECTED TOWARDS TREES TO BE PROTECTED. CONSTRUCTION STORMWATER SHALL NOT POND WITHIN A TREE'S CRITICAL ROOT ZONE.

#### TEMPORARY EROSION AND SEDIMENTATION CONTROL MAINTENANCE REQUIREMENTS

- EROSION AND SEDIMENTATION CONTROL FACILITIES SHALL BE INSPECTED AFTER EACH STORM EVENT AND DAILY DURING PROLONGED RAINFALL.
- 2. NECESSARY REPAIRS OR REPLACEMENT OF FACILITIES SHALL BE ACCOMPLISHED PROMPTLY.
- 3. SEDIMENT DEPOSITS SHALL BE REMOVED AFTER EACH STORM EVENT OR WHEN THE LEVEL OF DEPOSITION REACHES APPROXIMATELY ONE-HALF THE MAXIMUM POTENTIAL DEPTH.
- 4. SEDIMENT DEPOSITS REMAINING IN PLACE AFTER THE ESC FACILITIES ARE NO LONGER REQUIRED SHALL BE DRESSED TO CONFORM TO THE EXISTING GRADE, PREPARED AND SEEDED

#### GENERAL NOTES

- 1. ALL WORKMANSHIP AND MATERIALS SHALL CONFORM TO THE MOST CURRENT STANDARD SPECIFICATIONS FOR ROAD, BRIDGE AND MUNICIPAL CONSTRUCTION PREPARED BY WSDOT AND APWA.
- 2. ANY REVISIONS TO THE ACCEPTED CONSTRUCTION PLANS SHALL BE REVIEWED AND APPROVED BY THE COUNTY PRIOR TO IMPLEMENTATION IN THE FIELD.
- 3. THE CONTRACTOR SHALL MAINTAIN A SET OF THE ACCEPTED CONSTRUCTION DRAWINGS ON-SITE AT ALL TIMES WHILE CONSTRUCTION IS IN PROGRESS.
- 4. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING ADEQUATE TRAFFIC CONTROL AT ALL TIMES DURING CONSTRUCTION ALONGSIDE OR WITHIN ALL PUBLIC ROADWAYS. TRAFFIC FLOW ON EXISTING PUBLIC ROADWAYS SHALL BE MAINTAINED AT ALL TIMES, UNLESS PERMISSION IS OBTAINED FROM THE COUNTY FOR ROAD CLOSURE AND/OR DETOURS.
- 5. THE LOCATION OF EXISTING UTILITIES ON THIS PLAN IS APPROXIMATE ONLY. THE CONTRACTOR SHALL CONTACT THE "UNDERGROUND LOCATE" CENTER AT 811, AND NON-SUBSCRIBING INDIVIDUAL UTILITY COMPANIES 48 HOURS IN ADVANCE OF THE COMMENCEMENT OF ANY CONSTRUCTION ACTIVITY. THE CONTRACTOR SHALL PROVIDE FOR PROTECTION OF EXISTING UTILITIES FROM DAMAGE CAUSED BY THE CONTRACTOR'S OPERATIONS.
- 6. THE CONTRACTOR SHALL NOTIFY THE ENGINEER IN THE EVENT OF DISCOVERY OF POOR SOILS, GROUNDWATER OR DISCREPANCIES IN THE EXISTING CONDITIONS AS NOTED ON THE PLANS.

#### GENERAL ELECTRICAL NOTES

- 1. UNLESS OTHERWISE NOTED, ALL NEW CONDUCTORS SHALL BE XHHW-2 OR THHN/THWN
- 2. THE MINIMUM CABLE BENDING RADIUS SHALL BE TEN TIMES THE CABLE DIAMETER.
- 3. THE CONTRACTOR IS RESPONSIBLE FOR ARRANGING AND PROVIDING TEMPORARY LIGHTING FOR THE WORK AREAS.
- 4. ALL ELECTRICAL WORK SHALL COMPLY WITH THE LATEST EDITION OF NFPA70, THE NATIONAL ELECTRICAL CODE AND WAC 296-46B.
- 5. ANY WORK INSTALLED INCORRECTLY OR BEFORE APPROVAL HAS BEEN OFFICIALLY GRANTED FOR THE ITEMS AT ISSUE SHALL BE CORRECTED BY THE CONTRACTOR AT NO CHARGE TO THE BREMERTON SCHOOL DISTRICT.
- 6. THE CONTRACTOR SHALL KEEP THE WORK AREA CLEAN AND REMOVE ALL REFUSE FROM THE WORK SITE DAILY.
- 7. ALL NEW CIRCUIT BREAKERS SHALL BE RATED FOR THE AVAILABLE FAULT CURRENT AT EACH LOCATION. IN THE CASE OF ENCLOSED CIRCUIT BREAKERS INSTALLED AHEAD OF THE MAIN SWITCHBOARD OR PANEL BREAKER, MATCH OR EXCEED THE RATING OF THAT MAIN BREAKER. FOR CIRCUIT BREAKERS INSTALLED IN EXISTING PANEL SPACES. MATCH THE EXISTING RATING OF THE OTHER EXISTING BREAKERS.
- 8. UPDATE ALL PANEL SCHEDULES AFFECTED BY THIS PROJECT TO REFLECT THE NEW CONDITIONS.
- 9. ALL MATERIALS AND EQUIPMENT FURNISHED BY THE CONTRACTOR AND INSTALLED IN THIS PROJECT SHALL BE NEW.
- 10. ALL EXTERIOR LIGHTING AND SWITCHES SHALL BE IN NEMA 3R ENCLOSURES.
- 11. PROVIDE LABELS FOR EACH DISCONNECT SWITCH. LABELS SHOULD INDICATE 'SUPPLIED FROM PANELBOARD #X IN ROOM XX'.
- 12. PROVIDE PULL BOXES AND JUNCTION BOXES TO FACILITATE THE INSTALLATION OF WIRING (IN ADDITION TO ANY SHOWN ON DRAWINGS)
- 13. CONTRACTOR SHALL PROVIDE PROTECT CLOSE OUT DOCUMENTATION IN ACCORDANCE WITH WSEC PARAGRAPH C102.6.3.

| CIVIL SYMBOL LEGEND |                         |  |
|---------------------|-------------------------|--|
| SYMBOL              | DESCRIPTION             |  |
| w                   | PROPOSED WATER          |  |
| ——s—                | PROPOSED SANITARY SEWER |  |
| w                   | EXISTING WATER          |  |
| s                   | EXISTING SANITARY SEWER |  |
| D                   | EXISTING STORM DRAIN    |  |
| — -FM- —            | EXISTING FORCE MAIN     |  |
| G                   | EXISTING GAS            |  |
|                     | EXISTING POWER          |  |
| x                   | EXISTING FENCE          |  |
| ///                 | EXISTING ASPHALT EDGE   |  |
| 0                   | UNDERGROUND SEWER VAULT |  |
| X                   | SET SCRIBE              |  |
|                     | FOUND SURFACE MONUMENT  |  |
|                     | SET HUB AND TACK        |  |
| <b>→</b> <          | SET MAG NAIL            |  |
|                     | SET NAIL                |  |
|                     | GAS METER / REGULATOR   |  |
|                     | CONIFER TREE            |  |
|                     | CATCH BASIN             |  |
|                     | AREA DRAIN              |  |
|                     | MANHOLE STORM           |  |
| (ii)                | SEWER CLEANOUT          |  |
| 0                   | MANHOLE SEWER           |  |
| Р                   | POWER VAULT             |  |
| -,0,-               | LIGHT                   |  |
|                     | BENCH                   |  |
|                     | IRRIGATION VALVE        |  |
| Д                   | FIRE HYDRANT            |  |

| ELECTRICAL SYMBOL LEGEND |  |
|--------------------------|--|
| SYMBOL                   | DESCRIPTION  |
|                          | EXISTING TO REMAIN LINETYPE  |
| ////                     | EXISTING TO BE REMOVED (DASH SCALE VARIES)   |
|                          | NEW ELECTRICAL CABLING PROVIDE (2)#12 AND A #12 GROUND UNLESS OTHERWISE NOTED  |
| ×-##                     | ELECTRICAL CABLING HOMERUN 'X' REPRESENTS PANEL NAME, '##' REPRESENTS CIRCUIT NUMBER, LONG TICK REPRESENTS NEUTRAL, SHORT TICK REPRESENTS HOT CONDUCTOR. |
| F                        | FUSED DISCONNECT. REFER TO ASSOCIATE FLAG NOTES FOR VOLTAGE/AMPERAGE RATING AND ADDITIONAL INFORMATION   |
| M                        | NON-FUSED DISCONNECT. REFER TO ASSOCIATE FLAG<br>NOTES FOR VOLTAGE/AMPERAGE RATING AND ADDITIONAL<br>INFORMATION   |
|                          | PIN AND SLEEVE RECEPTACLE. REFER TO ASSOCIATED FLAG NOTES FOR VOLTAGE/AMPERAGE RATING AND ADDITIONAL INFORMATION.  |
| Ф                        | DUPLEX RECEPTACLE<br>PROVIDE (2)#12 AND A #12 GROUND UON.  |
| <b>₩</b>                 | GFCI DUPLEX RECEPTACLE   |
| Ф                        | HALF-SWITCHED DUPLEX RECEPTACLE  |
| ф                        | FULL-SWITCHED DUPLEX RECEPTACLE  |
| =                        | ISOLATED GROUND RECEPTACLE   |

STEEL POST

FINAL RE-SUBMITTAL

2020-JUL-29

SHEET IS 22x34 ANSI D IF PRINTING 11x17 USE 50% SCALE FACTOR

SHT NO 2 OF 7

SCHOOL SBO, WA

ARY

SEE EE

ITSAP PRTAB SON F

POF PAL VAL

<u>N</u>

DRAWN:

DESIGNED:

CHECKED:

ISSUE DATE

REVISIONS

JOB NO

SHT TITLE

LEGENDS

GENERAL NOTES, ABBREVIATIONS, AND SYMBOL

EA

ቧ

HED

MWM


RBG

29 JUL 2020


FANKS004

CE

MOLL





Permit Number: 20-02306




NORTH KITSAP NEW PORTAB DER PEARSON I HILDER PE CENTRAL 5650 MWM RBG SMH29 JUL 2020

/ SCHOOL -SBO, WA 9









SHEET IS 22x34 ANSI D IF PRINTING 11x17 USE 50% SCALE FACTOR SHT NO 5 OF 7

C200

Permit Number: 20-02306

NORTH KITSAP SCHOOL DISTRICT
NEW PORTABLE INSTALLATION
HILDER PEARSON ELEMENTARY SCHOOL
15650 CENTRAL VALLEY RD NW, POULSBO, WA 98370

ART

DRAWN: MWM
DESIGNED: RBG
CHECKED: SMH


ISSUE DATE

29 JUL 2020

REVISIONS

JOB NO FANKSOO4

SHT TITLE **DETAILS** 



FINAL RE-SUBMITTAL

2020-JUL-29

#### SHEET NOTES

1. REFER TO ONE LINE DIAGRAM FOR CONDUIT AND CONDUCTOR SIZES.

#### **FLAG NOTES**

PROVIDE AND INSTALL NEW CIRCUIT IN CONDUIT FROM EXISTING SWITCHBOARD 'H' TO NEW PORTABLE TRANSFORMER. CORE DRILL WALL AND ROUTE CONDUIT ABOVE CEILING TO GYM AND THEN ALONG WALL AS SHOWN. CONFIRM ROUTE WITH NORTH KITSAP SCHOOL DISTRICT REPRESENTATIVE.

2>> ROUTE CONDUIT IN TRENCH FROM WALL TO NEW TRANSFORMER. INSTALL CONDUIT 24" DEEP MINIMUM. RESTORE ASPHALT. REFER TO DETAIL 1 ON SHEET C200 FOR ADDITIONAL INFORMATION.

NEW 50 KVA 480-120/240V SINGLE PHASE TRANSFORMER.


4>> ROUTE CONDUIT IN TRENCH FROM NEW FUSED DISCONNECT SWITCH TO NEW GRINDER PUMP DISCONNECT SWITCH IN GRINDER PUMP VAULT. INSTALL CONDUIT 24" DEEP MINIMUM. RESTORE ASPHALT. REFER TO DETAIL 1 ON SHEET C200 FOR ADDITIONAL INFORMATION.

5 PROVIDE AND INSTALL 30A/240V FUSED DISCONNECT FOR GRINDER PUMP CONNECTIÓN. DISCONNECT SHALL BE MOUNTED WITHIN 10' OF TRANSFORMER.


6 PROVIDE AND INSTALL 30A/240V NON-FUSED DISCONNECT FOR GRINDER PUMP CONNECTION.

7 THE GRINDER PUMP INSTALLATION IS CONSIDERED A CLASS 1, DIVISION 1 AREA FROM THE PUMP ALARM PANEL TO THE PUMP MOTOR. A SEAL OFF AND J-BOX MUST BE LOCATED BEFORE THE ALARM PANEL TO ISOLATE THE HAZARDOUS LOCATION. THE NON-FUSED DISCONNECT SWITCH MAY BE USED FOR THIS PURPOSE. THE PUMP POWER CABLES ARE NOT SUITABLE FOR DIRECT BURIAL AND MUST BE RUN IN RIGID METAL CONDUIT OR INTERMEDIATE METAL CONDUIT THREADED ONLY. INSTALLATION MUST MEET ALL REQUIREMENTS OF THE NEC, SECTION 501. REFER TO THE PUMP INSTALLATION MANUAL FOR FURTHER DIRECTIONS.

8 PROVIDE AND INSTALL A 200 AMP/ 240 VOLT SINGLE PHASE FUSED DISCONNECT SWITCH WITHIN 10 FEET OF THE TRANSFORMER AND ROUTE CIRCUIT TO PORTABLE CLASSROOM PANELBOARD. REFER TO BLAZER DRAWINGS FOR ADDITIONAL INFORMATION.



ENLARGED GRINDER PUMP VAULT PLAN



98370

P SCHOOL DISTRICT
BLE INSTALLATION
I ELEMENTARY SCHOOL
Y RD NW, POULSBO, WA 9

NORTH KITSAP NEW PORTABI HILDER PEARSON E 15650 CENTRAL VALLEY F

ISSUE DATE 29 JUL 2020

REVISIONS

JOB NO

FANKS004 SHT TITLE ELECTRICAL ENLARGED PLANS


SHT NO 6 OF 7

IF PRINTING 11x17 USE 50% SCALE FACTOR

SHEET IS 22x34 ANSI D



1 NEW CIRCUIT BREAKER FOR EXISTING SIEMENS SWITCHBOARD. PROVIDE NEW 150A, 2-POLE (65KAIC AT 480Y/277V). CONFIRM COMPARABILITY WITH THE EXISTING EQUIPMENT PRIOR TO ORDERING.



98370 P SCHOOL DISTRICT
BLE INSTALLATION
I ELEMENTARY SCHOOL
Y RD NW, POULSBO, WA 9 NORTH KITSAP SCH NEW PORTABLE II HILDER PEARSON ELEI 0 CENTRAL VALLEY RD N 5650

MWM DRAWN: DESIGNED: DPK SMH CHECKED:

ISSUE DATE


29 JUL 2020 REVISIONS

JOB NO FANKS004


SHT TITLE ELECTRICAL SINGLE LINE AND PANEL SCHEDULES

SHT NO 7 OF 7

SHEET IS 22x34 ANSI D IF PRINTING 11x17 USE 50% SCALE FACTOR



PARTIAL SINGLE LINE DIAGRAM E301 Scale: NTS



GROUNDING DETAIL

FINAL RE-SUBMITTAL 2020-JUL-29

Permit Number: 20-02306

E301 Scale: NTS

PER NEC 220-87 and WAC 296-46B-900(3)(j) Recorded Peak Demand on Date: 06 / 04 / 2019 Study Dates: From \_\_/\_\_/\_\_ Power Factor Apparent Peak Demand NEC 220-87 adjustment factor

354

(P.F.) 0.85 KVA 206 1.25 257 Adjusted Peak Demand KVA Seasonally Adjusted Peak Demand 257 Occupancy adjustment factor ●● 257 Occupancy Adjusted Peak Demand Other adjustment factor(s) ●● Total Peak Demand 257 New Calculated Load Added 37 Metered demand based CALCULATED LOAD:

PEAK DEMAND CALCULATION WORKSHEET